

## CLAIMS

5

10

15

20

25

30

*Sub  
at  
DV*

1. A scooter assembly, comprising:
  - (a) a scooter comprising a running board supported by a front wheel and a rear wheel, said front wheel being connected to a handle bar by means of a steering shaft;
  - (b) a motor assembly detachably mounted to said scooter comprising a case and a motor, said case housing a battery and said motor being electrically connected to said battery and said motor having a shaft for engagement with one of said wheels; and
  - (c) a biasing mechanism operably associated with said motor and at least one of said scooter and said case to urge said motor shaft into engagement with one of said wheels.
2. The scooter assembly of claim 1 wherein said motor assembly is detachably mounted to said steering shaft and said motor shaft engages said front wheel.
3. The scooter assembly of claim 1 wherein said biasing mechanism is an elastic band.
4. The scooter assembly of claim 1 wherein said motor is housed within said case.
5. The scooter assembly of claim 1 wherein said motor is external of said case.

108220" 06ET4660

sub  
a2

6. The scooter assembly of claim 1 wherein said scooter further comprises a pin and said case has a bearing portion for receiving said pin, so that said case is capable of pivoting with respect to said scooter.

5

7. The scooter assembly of claim 1 further comprising a clamp for attaching said case to said scooter.

10

8. The scooter assembly of claim 1 wherein said case is vertically adjustable with respect to said front wheel.

sub  
a3

15

9. The scooter assembly of claim 1 further comprising a control mechanism attached to said handle bar to control operation of said scooter.

20

10. The scooter assembly of claim 1 further comprising a control circuit and a wheel sensor, said control circuit controlling operation of said motor in response to a signal received from said wheel sensor.

25

11. The scooter assembly of claim 1 further comprising a control circuit and a current sensor capable of monitoring current flow to said motor, said control circuit controlling operation of said motor in response to a signal received from said current sensor.

30

12. A method for operating a motorized scooter assembly, comprising:

(a) providing a scooter comprising a running board supported by a front wheel and a rear wheel, said front wheel being connected to a handle bar by means of a steering shaft;

35

(b) providing a motor assembly comprising a case and a motor, said case housing a

00941390.082801

battery and said motor being electrically connected to said battery and said motor having a shaft for engagement with one of said wheels;

- 5 (c) detachably mounting said motor assembly to said scooter; and
- (d) biasing said motor with respect to at least one of said scooter and said case to urge said motor shaft into engagement with said one of said wheels.

10 13. The method of claim 12 wherein said step of detachably mounting said motor assembly to said scooter comprises connecting an elastic band to said case, said elastic band passing around a portion of said scooter.

15 *Sub A4* 14. The method of claim 12 wherein said scooter further comprises a pin and said case further comprises a bearing portion, and said step of detachably mounting said motor assembly to said scooter comprises receiving said pin within said bearing portion.

20 15. The method of claim 12 wherein said step of detachably mounting said motor assembly to said case comprises attaching said case to a clamp mounted to said scooter.

25 16. The method of claim 12 further comprising the step of detaching said motor assembly from said scooter when said battery is discharged.

30 *Sub A5* 17. The method of claim 12 further comprising the step of controlling operation of said motor in response to turning of one of said wheels.

35

00041390-082801

get a)

sub  
a7

sub  
a7

sub  
a7


35            22. The scooter assembly of claim 21 wherein  
said biasing mechanism is an elastic band.

23. The scooter assembly of claim 21 wherein said biasing mechanism is a spring.

5 24. The scooter assembly of claim 21 wherein said case is detachably mounted to said steering shaft.

25. The scooter assembly of claim 21 wherein said case and said motor form a motor assembly that is detachably mounted to said steering shaft.

10

 26. The scooter assembly of claim 21 wherein said scooter further comprises a pin and said case has a bearing portion for receiving said pin, so that said case is capable of pivoting with respect to said scooter.

15

27. The scooter assembly of claim 21 further comprising a clamp for attaching said case to said steering shaft.

20

28. The scooter assembly of claim 21 wherein said case is vertically adjustable with respect to said front wheel.

25 29. The scooter assembly of claim 21 further comprising a control mechanism attached to said handle bar to control operation of said scooter.

30 30. The scooter assembly of claim 21 further comprising a control circuit and a wheel sensor, said control circuit controlling operation of said motor in response to a signal received from said wheel sensor.

35 31. The scooter assembly of claim 21 further comprising a control circuit and a current sensor capable of monitoring current flow to said motor, said control circuit controlling operation of said motor in response to a signal received from said current sensor.

00941390 002200